



# ROYAL GLOBAL ENERGY

RGE's core business Oil, Gas, Refining and Petrochemicals

## Product Name: Dry Pyrolysis Gasoline

Component	Unit	Specification	Analysis Method
Aromatics	wt%	max 50	...
Benzene	wt%	max 30	...
Density at 15.6C	gr/cm3	0.8-0.84	ASTM D4052
FBP	°C	max 225	ASTM D86
IBP	°C	min 33	ASTM D86
R.V.P	kpa	40-65	ASTM D6378
Paraffines	wt%	max 21	...
Isoparaffines	wt%	max 21	...
Naphtenes	wt%	max 2	...
Olefins	wt%	max 20	...
Total Sulfur	mg/kg	350	ASTM D5453
Gum Content	mg/100ml	max 50	...
Lead Content	ppb	max 30	...
Residue	wt%	...	ASTM D86
5% Recovery	°C	min 45	ASTM D86
10% Recovery	°C	...	ASTM D86
20% Recovery	°C	...	ASTM D86
30% Recovery	°C	...	ASTM D86
40% Recovery	°C	...	ASTM D86
50% Recovery	°C	...	ASTM D86
60% Recovery	°C	...	ASTM D86
70% Recovery	°C	...	ASTM D86
80% Recovery	°C	...	ASTM D86
90% Recovery	°C	min 175	ASTM D86
Recovery	°C	...	ASTM D86
Color Sybolt	...	-16	...