

Crystal Melamine



Melamine is ideal for use in high-performance products like wood-based panels, laminates, coatings, molding powders and flame-retardants. Melamine is used in impregnating adhesive resins in the wood-processing industry.

Melamine also plays a role in a wide range of flame resistant materials, including; upholstery textiles, intumescent paints, fabrics used in uniforms worn by firefighters and industrial workers, and a wide variety of residential, commercial, and industrial fire block materials.



Packing:

Poly Bag



Jumbo bags



TYPICAL SPECIFICATIONS

Specification	Range
Melamine Content	WT percent bigger than 99.8 %
Water Content	WT percent 0.15max.
PH	7.5 min. 9.5 max.
Color (pt-co)	30 max.
Turbidity (Kaoline)	30 max.
Size	Percent 80(80 MESH) min.
H2O Solubility 20 Degree	Clear
Ash Conter	WT percent smaller than 0.05ma
Hydrophob test	30-70 min max.
Formaldehyde Solubility	Clear



RGE's core business Oil, Gas, Refining and Petrochemicals



Container Shipment:

Minimum Order:- 2 CNTRs



CAUSTIC SODA FLAKES

Caustic soda is highly hygroscopic and soluble in water and alcohols. Caustic soda flake is one of the main raw materials in the chemical industry. Sodium hydroxide is used in most of industries, for example: cosmetics, petrochemical, metallurgical, textile, food or in water treatment.



Packaging:-

1MT Jumbo bags



50kg bags



TYPICAL SPECIFICATIONS

Property	Result	
	Lye	Flakes
Appearance	Clear, colorless liquid	
Sodium Hydroxide Concentration	47.5%	98%
Purity	99.6%	99.6%
Sodium Carbonate Content	0.30%	0.30 – 0.35%
Chloride Content	0.03%	0.03%
Sulfate content	Traces	Traces
Iron	10 Max	10 – 15
Copper	Nil	Nil
Manganese	Nil	Nil
Matter insoluble in water%	Nil	Nil

Container Shipment:

Minimum Order:- **2 CNTRs**

Royal Global Energy