

White Oil



White Oil is used as a blending base for Pharmaceutical and Cosmetic Products such as creams, lotions, hair oils, petroleum jelly, ointments, laxatives etc. It also find application in many other industrial segments such as polystyrene manufacturing, food packaging industries, protective coatings for fruits and vegetables, food preservatives, veterinary preparations etc.



Packing:

Drums



Flexi Tank



© Image copyright Philton Polythene Converters Ltd.
Copyright WILL be enforced.

TYPICAL SPECIFICATIONS

Pharma Grade

Analysis	Units	Test Method	Limits	
			Min	Max
Appearance	-	Visual	Transparent, Colorless, Bright and clear oily liquid	
Color	Say Bolt	ASTM D156	+25	-
Odor	-		Odorless	
Density @ 29.5°C	Gms/cc	ASTM D1298	0.82	0.85
Kin Viscosity@40°C	Cst	ASTM D445	7.50	8.50
Flash Point COC	°C	ASTM D92	140	-
Pour Point	°C	ASTM D97	-	-19
Ultraviolet Absorbance	Abs/cm	CFR 178.3620(b)		
280 - 289nm			-	4.0
290 - 299nm			-	3.3
300 - 329nm			-	2.3
330 - 350nm			-	0.8
Acidity or Alkalinity	-	BP/EP	Not more than 0.1ml of 0.1M NaOH	
Readily Carbonisable Substances	-	BP/USP/EP		Pass
Solid Paraffin	-	BP/USP/EP		Pass
Polycyclic Aromatic Hydrocarbon	-	BP/USP/EP		Pass

Royal Global Energy

Technical Grade

Analysis	Units	Test Method	Limits	
			Min	Max
Appearance	-	Visual	Transparent, Colorless, Bright and clear oily liquid	
Color	Say Bolt	ASTM D156	+25	-
Odor	-		Odorless	
Density @ 29.5°C	Gms/cc	ASTM D1298	0.82	0.85
Kin Viscosity@40°C	Cst	ASTM D445	7.50	8.50
Flash Point COC	°C	ASTM D92	140	-
Pour Point	°C	ASTM D97	-	-19
Ultraviolet Absorbance	Abs/cm	CFR 178.3620(b)		
280 - 289nm			-	4.0
290 - 299nm			-	3.3
300 - 329nm			-	2.3
330 - 350nm			-	0.8



RGE's core business Oil, Gas, Refining and Petrochemicals



RGE

Royal Global Energy

Container Shipment:

Minimum Order:- **10 CNTRs**

Bulk Shipment:

Minimum Order:- **2 KT**

Maximum Order:- **5 KT**